

Daily Disposables

Reusable Disposables

ACUVUE® Products	ACUVUE® OASYS 1-DAY with Hydraluxe™ Technology	ACUVUE® OASYS 1-DAY for ASTIGMATISM*	1-DAY ACUVUE® TruEye®	1-DAY ACUVUE® MOIST®	1-DAY ACUVUE® MOIST® MULTIFOCAL	1-DAY ACUVUE® MOIST® for ASTIGMATISM*	1-DAY ACUVUE® DEFINE® with LACREON®	ACUVUE® OASYS with HYDRACLEAR® Plus	ACUVUE® OASYS for ASTIGMATISM*	ACUVUE® VITA™	ACUVUE® VITA™ for ASTIGMATISM*	
	Radiant Sweet™, Radiant Chic™, Radiant Bright™, Radiant Charm™, Accent Style, Vivid Style, Natural Shine™						Fresh Honey, Fresh Blue, Fresh Green, Fresh Grayzel					
Replacement	1 day							2 weeks		1 month		
Key Selling Point	Provides unbeaten comfort and minimises eye tiredness throughout demanding days	Sharp and stable vision with exceptional comfort	Clear and healthy eyes, comparable to wearing no lenses at all	Provides exceptional comfort all day	A sharper than ever vision experience for eyes with presbyopia	Excellent comfort and visual acuity for patients with Astigmatism	Let your eyes shine all day with healthy radiance	Superior comfort and performance in challenging environments	Excellent comfort and visual acuity for patients with Astigmatism	Exceptional comfort all month long		
Retail Price/ Box	RM 180	RM 220	RM 162	RM 134	RM 228	RM 170	RM 162	RM 162	RM 124	RM 170	RM 180	RM 220

Lens Properties

Lens Material	senofilcon A		narafilcon A		etafilcon A			senofilcon A		senofilcon C		
Oxygen Flux (Open Eye)	98%			88%			98%					
Center Thickness @ -3.00D (mm)	0.085	0.080	0.085	0.084	0.09	0.084		0.07	0.08	0.07	0.08	
UV Blocking †	>99% UVB >96% UVA			97% UVB 82% UVA			>99% UVB >96% UVA					
Visibility Tint	Yes						No			Yes		
Inside-Out Mark	Yes ("123")	No (Scribed at 6 & 12 o'clock)	Yes ("123")		No (Scribed at 6 & 12 o'clock)	No		Yes ("123")	No (Scribed at 6 & 12 o'clock)	Yes ("123")	No (Scribed at 6 & 12 o'clock)	

Lens Specifications

Lens Parameter	8.5 & 9.0/14.3	8.5/14.3	8.5 & 9.0/14.2	8.4/14.3	8.5/14.5	8.5/14.2	8.4 & 8.8/14.0	8.6/14.5	8.4 & 8.8/14.0	8.6/14.5	
Full Power Range	-0.50 to -12.00 +0.50 to +8.00	Plano to -9.00 +0.25 to +4.00	-0.50 to -12.00 +0.50 to +6.00	Plano to -9.00 +0.25 to +6.00	Plano to -9.00 +0.25 to +4.00	Plano to -9.00 (no -0.25)	-0.50 to -12.00 +0.50 to +8.00	Plano to -9.00 +0.25 to +6.00	-0.50 to -12.00 +0.50 to +8.00	Plano to -9.00 +0.25 to +4.00	
Low to Mid Minus											
Sph (in 0.25D steps)	-0.50D to -6.00D	Plano to -6.00D	-0.50D to -6.00D	-0.50D to -6.00D	Plano to -9.00D	Plano to -6.00D	Plano to -6.00D (no -0.25D)	-0.50D to -6.00D	Plano to -6.00D	-0.50D to -6.00D	Plano to -6.00D
Cyl & Axis **	Cyl: -0.75D, -1.25D, -1.75D Axis: 10° to 180° (in steps of 10°) Cyl: -2.25D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°					Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 60°, 70°, 80°, 90°, 100°, 110°, 120°, 160°, 170°, 180° Cyl: -2.25D Axis: 20°, 90°, 160°, 180°		Cyl: -0.75D, -1.25D, -1.75D, -2.25D, -2.75D Axis: 10° to 180° (in steps of 10°)		Cyl: -0.75D, -1.25D, -1.75D Axis: 10° to 180° (in steps of 10°) Cyl: -2.25D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°	
					LOW +0.75D to +1.25D MID +1.50D to +1.75D HIGH +2.00D to +2.50D						
High Minus											
Sph (in 0.50D steps)	-6.50D to -12.00D	-6.50D to -9.00D	-6.50D to -12.00D	-6.50D to -12.00D		-6.50D to -9.00D	-6.50D to -12.00D	-6.50D to -9.00D	-6.50D to -12.00D	-6.50D to -9.00D	-6.50D to -9.00D
Cyl & Axis **	Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°					Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°		Cyl: -0.75D, -1.25D, -1.75D, -2.25D, -2.75D Axis: 10° to 180° (in steps of 10°)		Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°	
Plus Power											
Sph (in 0.25D steps)		+0.25D to +4.00D		+0.50D to +6.00D	+0.25D to +6.00D	+0.25D to +4.00D	+0.50D to +6.00D	+0.25D to +6.00D	+0.50D to +6.00D	+0.25D to +4.00D	+0.25D to +4.00D
Sph (in 0.50D steps)							+6.50D to +8.00D		+6.50D to +8.00D		
Cyl & Axis **		Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°				Cyl: -0.75D, -1.25D, -1.75D Axis: 20°, 70°, 90°, 110°, 160°, 180°		Cyl: -0.75D, -1.25D, -1.75D, -2.25D, -2.75D Axis: 10° to 180° (in steps of 10°)		Cyl: -0.75D, -1.25D, -1.75D Axis: 10°, 20°, 70°, 80°, 90°, 100°, 110°, 160°, 170°, 180°	
					LOW +0.75D to +1.25D MID +1.50D to +1.75D HIGH +2.00D to +2.50D						

Amended on 26th October 2021

** 3 weeks to indent if product is out-of-stock / for oblique axis.

† Help protect against transmission of harmful UV radiation to the cornea and into the eye. WARNING: UV-blocking contact lenses are NOT substitutes for protective UV-blocking eyewear such as UV-blocking goggles or sunglasses because they do not completely cover the eye and surrounding area. You should continue to use UV-blocking eyewear as directed. NOTE: Long-term exposure to UV radiation is one of the risk factors associated with cataracts. Exposure is based on a number of factors such as environmental conditions (altitude, geography, cloud cover) and personal factors (extent and nature of outdoor activities). UV-blocking contact lenses help provide protection against harmful UV radiation. However, clinical studies have not been done to demonstrate that wearing UV-blocking contact lenses reduces the risk of developing cataracts or other disorders. Consult your eye care practitioner for more information. Disposable contact lenses are medical devices and patients are subjected to an eye examination with consultation fees. Johnson & Johnson Vision (Malaysia) reserves the right to change any terms and conditions herein at any time without prior notice.

Johnson & Johnson Customer Service

Phone: 1800-22-8883

Fax: 603-77701230

Email: acuvue.order@its.jnj.com

Time: Monday-Friday, 8.30am-6pm